

40" x 48" MEDIUM-DUTY BULKPAK®

Produce ■ Caps/Closures ■ Metal Parts ■ Plastics and Rubber ■ Resins and Powders ■ Tools

The medium-duty BulkPak® 4048 GP Series was designed for a wide variety of product sizes, shapes and weights. It allows more parts to be handled, stored and shipped...with fewer containers and in fewer trips. The advanced design results in a consistent tare weight that improves inventory and shipping efficiencies. With a weight capacity 1,500-2,000 pounds, these containers are ideal for all types of food, industrial or beverage applications, as well as for international shipments. These containers are structural-foam molded in high-density polyethylene for durability. Custom protective dunnage is available for all ORBIS BulkPak containers.



Structural channel cover available for added product protection and secure stacking.

Structural foam base and sidewalls deliver strength and durability

CGP4048 (cover)

Ventilated sidewalls available on 32" and 46" models.



GP4048-50

GP4048-46

100% recyclable

All-plastic construction eliminates risk of rust.



GP4048-34

Full picture frame bottom reduces risk of "short forking".


Consistent tare weight



Cardholder



ID Plate



Label Placard*



Placard Board*



BulkPak Covers



Self-standing sidewall for safe and efficient assembly and collapse.



GP4048-46 Bev

40 x 48 MEDIUM-DUTY BULKPAK

- >> 4 heights: 34", 39", 46" and 50"
- >> Access Doors: 0, 1 or 2 doors on the 40" side (Door configurations vary by model)
- >> Base: All-plastic picture frame bottom or footcaps
- >> Deck: Solid deck on all sizes and ventilated deck on 46" models
- >> Sidewalls: Solid sidewalls on all sizes, ventilated sidewalls available on 46" models
- >> Cover: CGP4048-SC (structural channel molded)

BulkPak® 4048 GP Container Specifications (Upper Dimensions: English, Lower Dimensions: Metric)

Model	Outside Dimensions			Inside Dimensions		Product Clearance (F)	Collapsed Height	Container Capacity (lb.)	Weight (lb.)	Internal Volume (cu. ft)**	Maximum Loaded Stack		Return Ratio	Access Door Openings			
	L (A)	W (B)	H (C)	L (D)	W (E)						Static	Dynamic		Height		Width	
													Long Side	Short Side	Long Side	Short Side	
CONTAINERS																	
GP4048-34	48.0	40.0	34.0	45.0	36.5	27.7	13.7	2,000	137.0	27.9	6 high	3 high	2.56:1	N/A	15.0	N/A	24.0
	1219.2	1016.0	863.6	1143.0	927.1	703.6	348.0	900.0	61.7	0.78	N/A	N/A	N/A	N/A	381.0	N/A	609.6
GP4048-39	48.0	40.0	39.0	45.0	36.5	32.7	13.7	2,000	152.0	32.8	5 high	2 high	2.94:1	N/A	19.0	N/A	24.0
	1219.2	1016.0	990.6	1143.0	927.1	830.6	348.0	900.0	68.4	0.92	N/A	N/A	N/A	N/A	482.6	N/A	609.6
GP4048-46***	48.0	40.0	46.0	45.0	36.5	39.7	14.3	1,500	152.0	39.5	4 high	2 high	3.46:1	N/A	19.0	N/A	24.0
	1219.2	1016.0	1168.4	1143.0	927.1	1008.4	363.2	675.0	68.4	1.11	N/A	N/A	N/A	N/A	482.6	N/A	609.6
GP4048-46	48.0	40.0	46.0	45.0	36.5	39.7	14.3	1,500	156.0	39.5	4 high	2 high	3.46:1	N/A	19.0	N/A	24.0
	1219.2	1016.0	1168.4	1143.0	927.1	1008.4	363.2	675.0	70.2	1.11	N/A	N/A	N/A	N/A	482.6	N/A	609.6
GP4048-46 ^{Bev}	48.0	40.0	46.0	45.0	37.0	39.7	14.3	1,500	135.0	41.4	5 high	2 high	3.46:1	N/A	N/A	N/A	N/A
	1219.2	1016.0	1168.4	1143.0	939.8	1008.4	363.2	675.0	60.75	1.16	N/A	N/A	N/A	N/A	N/A	N/A	N/A
GP4048-50	48.0	40.0	50.0	45.0	36.5	43.7	17.7	1,500	177.0	43.4	4 high	2 high	2.89:1	N/A	19.0	N/A	24.0
	1219.2	1016.0	1270.0	1143.0	927.1	1110.0	449.6	675.0	79.7	1.22	N/A	N/A	N/A	N/A	482.6	N/A	609.6
COVER																	
CGP4048	48.2	40.2	2.6	48.0	40.0	0.8	N/A	N/A	16.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	1224.3	1021.1	66.0	1219.2	1016.0	20.3	N/A	N/A	2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Specifications (continued)

Model	Fork Openings				40' Container Quantities (w/o covers)		53' Truckload Quantities (w/o covers)	
	Height		Width		Collapsed	Assembled	Collapsed	Assembled
	Long Side (H)	Short Side (J)	Long Side (G)	Short Side (I)				
GP4048-34	3.25	3.25	11.8	11.8	147	63	240	90
	82.6	82.6	299.7	299.7	N/A	N/A	N/A	N/A
GP4048-39	3.25	3.25	11.8	11.8	147	42	240	60
	82.6	82.6	299.7	299.7	N/A	N/A	N/A	N/A
GP4048-43	3.25	3.25	11.8	11.8	105	42	180	60
	82.6	82.6	299.7	299.7	N/A	N/A	N/A	N/A
GP4048-46***	4.5	4.5	11.8	11.8	147	42	240	60
	114.3	114.3	299.7	299.7	N/A	N/A	N/A	N/A
GP4048-46	4.5	4.5	11.8	11.8	147	42	240	60
	114.3	114.3	299.7	299.7	N/A	N/A	N/A	N/A
GP4048-46 ^{Bev}	4.5	4.5	11.8	11.8	147	42	240	60
	114.3	114.3	299.7	299.7	N/A	N/A	N/A	N/A
GP4048-50	3.25	3.25	11.8	11.8	105	42	180	60
	82.6	82.6	299.7	299.7	N/A	N/A	N/A	N/A

- * Patented process #5,628,858 owned by The Kennedy Group.
 ** Internal volume calculated with cover.
 *** Ventilated sidewalls with footcaps. All other models have solid sidewalls with picture frame bottom base.

