



Hand pallet truck with flat forks **AM 15l**

Lift height: 120 mm / Capacity: 1500 kg

VDI table

Stand-on: 05/2020

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich				
	1.2	Manufacturer's type designation		AM 15I				
	1.3	Drive		Manual				
	1.4	Operation		Manual				
	1.5	Capacity/load	Q kg	1.500				
	1.6	Load centre distance	c mm	600	500	400	500	600
	1.9	Wheelbase	y mm	1.100	900	745	1.080	
Weights	2.1	Service weight	kg	74	72	71	61	65
	2.2	Axle load laden front/rear	kg	-			476 / 613	
	2.3	Axle load unladen front/rear	kg	-	60 / 28	-	60 / 28	
Wheels/suspension system	3.1	Tyres		C, N				
	3.2	Tyre size, front		Ø 170x50				
	3.3	Tyre size, rear		Ø 50x70				
	3.5	Wheels, number front/back (x=driven)		2/4				
	3.6	Tread width, front	b ₁₀ mm	109				
	3.7	Tread width, rear	b ₁₁ mm	370				
	Basic dimensions	4.4	Lift (h ₃)	h ₃ mm	120			
4.9		Height of tiller handle in drive position min./max.	mm	1.237				
4.14		Stand height, elevated	h ₁₂ mm	171				
4.15		Height, lowered	h ₁₃ mm	51				
4.19		Overall length	l ₁ mm	1.530	1.330	1.175	1.530	
4.20		Length including fork shank	l ₂ mm	380				
4.21.1		2. Overall width (b ₂)	b ₁ mm	520			680	
4.22		Fork dimensions	s/ e/l mm	38 / 150 / 1.150	38 / 150 / 950	38 / 150 / 795	38 / 150 / 950	38 / 150 / 1.150
4.25		Width across forks (dimension 1), WaF	b ₅ mm	520			680	
4.32		Ground clearance centre of wheelbase	m ₂ mm	13				
4.34		Aisle width (pallet 1000x1200 sideways)	A _{st} mm	1.584				
4.34.1		Aisle width (pallet 800x1200 length)	A _{st} mm	1.784				
4.35		Turning radius	W _a mm	1.274				
Performance data	5.3	Lowering speed laden/unladen	m/s	0.09 / 0.02				

- In accordance with VDI Guideline 2198 this data sheet provides details of the standard truck only. Non-standard tyres, different masts, optional equipment, etc. may result in different values.

The German production facilities in Norderstedt, Moosburg and Landsberg are certified.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet European safety requirements.



JUNGHEINRICH